

MasterJet

Fab Floor Indoor

Features

- Matt white, bead technology, anti-slip self-adhesive PET Fabric with excellent anti-scratch and anti-slip properties;
- Textured non-slip surface – P5 non-slip rating in accordance with AS 4586:2013 Slip resistance classification of new pedestrian surface materials, Appendix A - Wet Pendulum Test (report available on request);
- Choice of 2 adhesives:
 - Low tack removable for short pile commercial carpets and smooth internal hard floor surfaces;
 - High tack removable adhesive for textured internal hard floor surfaces.
- Perfect for retail shop campaigns, temporary events, sponsored targeted marketing, promotional events, wayfinding, point of purchase and facility safety flooring.

Technical Data

<p>PRINT SURFACE:</p> <ul style="list-style-type: none"> • Type/Colour/Surface • Thickness • Weight • Slip Rating 	<ul style="list-style-type: none"> • 100% Polyester (PET)/White/Embossed Bead Matte • 360 μ \pm 50 (incl. adhesive) • 240gsm \pm 50 (incl. adhesive) • P5 in accordance with AS 4586:2013 Slip resistance classification of new pedestrian surface materials, Appendix A - Wet Pendulum Test.
<p>ADHESIVE:</p> <ul style="list-style-type: none"> • Option 1 • Option 2 	<ul style="list-style-type: none"> • Low tack removable adhesive for short pile commercial carpet and smooth internal hard floor surfaces. • High Tack removable adhesive for rough internal floor surfaces.
<p>LINER:</p> <ul style="list-style-type: none"> • Type/Colour • Thickness • Weight 	<ul style="list-style-type: none"> • Kraft paper/White • 150 μ \pm 20 • 150gsm \pm 30

Technical Data Sheet

Technical Data cont.

Durability*	<ul style="list-style-type: none"> Up to 6 months indoor
Slip Rating	<ul style="list-style-type: none"> P5 in accordance with AS 4586:2013 Slip resistance classification of new pedestrian surface materials, Appendix A - Wet Pendulum Test
Printability	<ul style="list-style-type: none"> Latex, UV & eco-solvent wide format inkjet systems
Rolls Size	<ul style="list-style-type: none"> 1370mm x 30M and 1524mm x 30M
Core	<ul style="list-style-type: none"> 3 inch

Graphic application - recommendations	
Surface	<ul style="list-style-type: none"> Dust free, oil free, smooth, flat, internal hard floor surfaces and carpet (short pile commercial carpet only)
Temperature	<ul style="list-style-type: none"> 10°C - 30°C air and substrate, and 30% - 70% RH

The user is responsible for determining the product's suitability for the intended application. Data represents average values where applicable, and is not intended for specification purposes. All statements, technical information (including physical and chemical characteristics) and recommendations about Stick On Signs products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. Specifications may change without notice.

*Expected Durability is an estimate (based on the manufacturers testing) of how long the product (unprinted) may perform satisfactorily in a vertical application in temperate non-extreme conditions. Actual performance life will depend on media and surface preparation and exposure conditions. For example, the direction and angle of the graphic; in areas of long, high temperature exposure; in areas of high pollution or high altitudes, outdoor performance will be decreased. Note, there is no warranty associated with this estimate. Laboratory test reports available upon request at cost.

Stick On Signs liability for defective products shall not exceed the purchase price paid by the purchaser or user and under no circumstances shall Stick On Signs be responsible or liable for any direct or indirect consequential or incidental damages or charges (this includes but is not limited to labour, loss of profits, revenue, business, opportunity and so forth) foreseeable or otherwise caused by defects in the Stick On Signs product.