

MasterJet

Masterjet Printable Magnet

Features

- Available as a 0.5mm or 0.8mm magnet with a 0.1mm gloss white PVC printable face film;
- Easy to apply, reposition and remove – no requirement for a professional installer;
- Removable and reusable as many times as required;
- 0.5mm magnet is suitable for general magnetic work, fridges, POS and signage;
- 0.8mm magnet is perfect for car magnets and other applications requiring a stronger magnetic force;
- Printable with eco-solvent, solvent and UV ink systems;
- Recommended for indoor and outdoor applications;
- Available in 620mm x 30M and 1000mm x 15M and 1250mm x 15M rolls.

Technical Characteristics

| | | MAGO.5 | Remarks |
|--|----|--------------|------------|
| Thickness | | 0.5 | |
| Specific Gravity (g/cm ³) | | 3.6 | |
| Elongation (%) | MD | 112.5 ↑ | CNS 1441 |
| | CD | 25 ↑ | |
| Tensile Strength (kg/mm ²) | MD | 0.96 ↑ | |
| | CD | 0.4 ↑ | |
| Hardness (Shore A) | | 45 | |
| Vicinity Soft Temp | | 140° C | ASTM D1525 |
| Temperature Range | | -5° C - 80°C | ASTM D1790 |

| | | MAGO.8 | Remarks |
|--|----|--------------|------------|
| Thickness | | 0.8 | |
| Specific Gravity (g/cm ³) | | 3.6 | |
| Elongation (%) | MD | 112.5 ↑ | CNS 1441 |
| | CD | 25 ↑ | |
| Tensile Strength (kg/mm ²) | MD | 0.96 ↑ | |
| | CD | 0.5 ↑ | |
| Hardness (Shore A) | | 45 | |
| Vicinity Soft Temp | | 140° C | ASTM D1525 |
| Temperature Range | | -5° C - 80°C | ASTM D1790 |

The user is responsible for determining the product's suitability for the intended application. Data represents average values where applicable, and is not intended for specification purposes. All statements, technical information (including physical and chemical characteristics) and recommendations about Stick On Signs products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. Specifications may change without notice.

*Expected Durability is an estimate (based on the manufacturers testing) of how long the product (unprinted) may perform satisfactorily in a vertical application in temperate non-extreme conditions. Actual performance life will depend on media and surface preparation and exposure conditions. For example, the direction and angle of the graphic; in areas of long, high temperature exposure; in areas of high pollution or high altitudes, outdoor performance will be decreased. Note, there is no warranty associated with this estimate. Laboratory test reports available upon request at cost.

Stick On Signs liability for defective products shall not exceed the purchase price paid by the purchaser or user and under no circumstances shall Stick On Signs be responsible or liable for any direct or indirect consequential or incidental damages or charges (this includes but is not limited to labour, loss of profits, revenue, business, opportunity and so forth) foreseeable or otherwise caused by defects in the Stick On Signs product.