

# MasterJet

## Printable Floor Graphics

### Features

- 200 µm, printable white, dull polish PVC film with clear, permanent adhesive.
- Anti-slip, abrasion resistant surface, with R10 and P4 (AS 4586:2013) anti-slip certification.
- Direct Printable, no laminate required.
- Perfect for retail shop campaigns, temporary events, sponsored targeted marketing, promotional events, wayfinding, point of purchase and facility safety signage on hard internal floor surfaces.

### Technical Data

Test Items	units	Test method	Average value
Thickness PVC	Micron	GB/T6672-2001	200±5
Weight-Liner	g/m <sup>2</sup>	GB4669-1995	140±10
Weight -finished product	g/m <sup>2</sup>	GB4669-1995	445±20
Initial adhesive	N/25mm	FTM 9	≥11
24h, 180°peel	N/25mm	FTM 1	≥13
Dimensional stability MD	mm	FTM 14	≤1.5
Dimensional stability CD	mm	FTM 14	≤1.0
Tensile strength MD	N/25 mm	GB/T1040.1-2006	≥60
Tensile strength CD	N/25 mm	GB/T1040.1-2006	≥70
Construction temperature	°C		20±10
Applicable temperature	°C		-20~+70

Durability*	<ul style="list-style-type: none"> <li>• Up to 3 months</li> </ul>
Anti-Slip Rating	<ul style="list-style-type: none"> <li>• <u>R10</u> according to AS 4586:2013 Slip resistance classification of new pedestrian surface materials, Appendix D - Oil Wet Inclining Platform Test.</li> <li>• <u>P4</u> according to AS 4586:2013 Slip resistance classification of new pedestrian surface materials, Appendix A - Wet Pendulum Test.</li> </ul>
Printability	<ul style="list-style-type: none"> <li>• Latex, UV &amp; eco-solvent wide format inkjet systems</li> </ul>
Rolls Size	<ul style="list-style-type: none"> <li>• 1370mm x 25M and 1524mm x 25M</li> </ul>
Core	<ul style="list-style-type: none"> <li>• 3 inch</li> </ul>
Shelf Life	<ul style="list-style-type: none"> <li>• 12 months service life: stored in suitable conditions, preferably use within 6 months.</li> </ul>

## Technical Data Sheet

Graphic application - recommendations	
Surface	<ul style="list-style-type: none"> <li>Dust free, oil free, smooth, flat, internal hard floor surfaces.</li> </ul>

The user is responsible for determining the product's suitability for the intended application. Data represents average values where applicable, and is not intended for specification purposes. All statements, technical information (including physical and chemical characteristics) and recommendations about Stick On Signs products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. Specifications may change without notice.

\*Expected Durability is an estimate (based on the manufacturers testing) of how long the product (unprinted) may perform satisfactorily in a horizontal indoor application in temperate non-extreme conditions. Actual performance life will depend on media and surface preparation and exposure conditions. For example, the direction and angle of the graphic; in areas of long, high temperature exposure; in areas of high pollution or high altitudes, outdoor performance will be decreased. Note, there is no warranty associated with this estimate. Laboratory test reports available upon request at cost.

Stick On Signs liability for defective products shall not exceed the purchase price paid by the purchaser or user and under no circumstances shall Stick On Signs be responsible or liable for any direct or indirect consequential or incidental damages or charges (this includes but is not limited to labour, loss of profits, revenue, business, opportunity and so forth) foreseeable or otherwise caused by defects in the Stick On Signs product.

