SOLVENT/ECO-SOLVENT/UV/LATEX PRINTING



Certified for HP Latex Inks

ARTISAN 901SGSJ

• Weight: 11 osy / 373 gsm

• Thickness: 18 mil / 457 microns

• Composition: 35% cotton, 65% polyester

• Weave Construction: 2:1

• Finish: Semi-Glossy / Natural White

• Texture: Medium



Applications: Fine Art Reproduction, Photography

Roll Widths: 30" - 126" (76.2cm - 3.20m)



FREDRIX PRINTCANVAS.COM

PRODUCT SPECIFICATION SHEET INKJET PRINTING CANVASES

Style: 901SGSJ

Name: Artisan Item Master: 131xx

Canvas Construction: 65% poly / 35% cotton

Weave: 2 x 1

Coatings: Acrylic/Latex Primers

Semi-Gloss Ink Receptive

Appearance: White

Texture: Medium

Finish Weight (oz): 11

(gsm): 373

Thickness (mils): 18

(microns): 457

Whiteness: 81

Brightness: 84

L: 91

a: 0

b: 0

Gloss 60°: 5

This canvas is designed for digital printing applications using solvent based ink sets. Although designed for all printers using these ink sets, actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of $70^{\circ}\text{F} \pm 5^{\circ}\text{F}$ and relative humidity of 50% RH $\pm 3\%$ RH The shelf life is 1 year at recommended temperature and humidity.

Tara Materials guarantees only the canvas itself against defects in quality or workmanship. No other warranty is expressed or implied.



INQUIRIES:

Phone: 1-800-241-8129 Ext. 175 (USA) or +1-770-963-5256 Ext. 160 (INTL)

Fax: 1-800-882-TARA (8272) or +1-770-963-1044 (INTL)

General Inquiries:

rluepke@taramaterials.com

International Inquiries:

mmorel@taramaterials.com

SOCIAL:

Facebook: @FredrixPrint facebook.com/fredrixprint Instagram: @FredrixPrintCanvas

instagram.com/ fredrixprintcanvas

LinkedIn: @Fredrix-Print-Canvas linkedin.com/company /fredrix-print-canvas

