

SOLVENT/ECO-SOLVENT/UV/LATEX PRINTING



Certified for
HP Latex Inks

SELECT 901SJ

- Weight: 11 oz / 366 gsm
- Thickness: 18.5 mil / 470 microns
- Composition: 35% cotton, 65% polyester
- Weave Construction: 2:1
- Finish: Matte / Natural White
- Texture: Medium



Applications: High Volume Art Reproduction, Photography, High end POP/Décor
Roll Widths: 30" - 126" (76.2cm - 3.20m)

FREDRIX
CANVAS

FREDRIXPRINTCANVAS.COM

PRODUCT SPECIFICATION SHEET INKJET PRINTING CANVASES

Style:	901SJ
Name:	Select
Item Master:	1097xxx
Canvas Construction:	65% poly / 35% cotton
Weave:	2 x 1
Coatings:	Acrylic/Latex Primers Ink Receptive
Appearance:	Natural White
Texture:	Medium
Finish Weight (oz):	11
(gsm):	366
Thickness (mils):	18.5
(microns):	470
Whiteness:	81
Brightness:	85
L:	94
a:	-0.2
b:	1.5
Gloss 60°:	Matte

This canvas is designed for digital printing applications using solvent based ink sets. Although designed for all printers using these ink sets, actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. The shelf life is 1 year at recommended temperature and humidity.

Tara Materials guarantees only the canvas itself against defects in quality or workmanship. No other warranty is expressed or implied.



INQUIRIES:

Phone: 1-800-241-8129

Ext. 175 (USA) or

+1-770-963-5256

Ext. 160 (INTL)

Fax: 1-800-882-TARA (8272) or

+1-770-963-1044 (INTL)

General Inquiries:

rluepke@taramaterials.com

International Inquiries:

mmorel@taramaterials.com

SOCIAL:

Facebook: @FredrixPrint

facebook.com/fredrixprint

Instagram: @FredrixPrintCanvas

instagram.com/

fredrixprintcanvas

LinkedIn: @Fredrix-Print-Canvas

linkedin.com/company

/fredrix-print-canvas